

Safety Data Sheet

AIRFLOW MARKER SMOKE GENERATOR

IDENTIFICATION OF THE SUBSTANCE / MIXYURE AND COMPANY OR **SECTION 1. UNDERTAKING**

Product Identifier

1.1. Tradename: AIRFLOW MARKER SMOKE GENERATOR

Contains Potassium chlorate and 2 Methyl Anthraquinone

UFI: 1X60-V0M1-400Q-YEDC

Relevant identified uses of 1.2.

the substance or mixture and

uses advised against

Airflow Marker Smoke Generator (FU)

1.3. Details of the supplier of the safety data sheet

Octavius Hunt Ltd Company

Redfield, BRISTOL, BS5 9NQ, UK

+44 (0) 117 955 5304 Phone Fax +44 (0) 117 955 7875 Website www.octaviushunt.co.uk Email info@octavius-hunt.co.uk

1.4. **Emergency**

NHS 111

telephone

number +44 (0) 117 955 5304 (Weekdays, Not 24hr)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

- Classification (Regulation (EC) No 1272/2008) [CLP/GHS]: Sens Skin. 1. H317; Aquatic Chronic 3. H412
- Additional Information: For full text of Hazard and EU Hazard-statements: see section 16

2.2 Label elements

UFI: 1X60-V0M1-400Q-YEDC



Signal word: WARNING

SECTION 2: HAZARDS IDENTIFICATION (....)

Warning H statements:

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary P statements:

Prevention:

P261 Avoid breathing dust/fume.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container as hazardous material according to current regulations.

Supplemental Hazard Information (EU)

- None

2.3. Other hazards:

The mixture contains Potassium Chloride which in contact with an acid gives off toxic gases. The mixture contains powder; all the organic powders may present an explosion hazard when dispersed in air.

- SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances: N.A.

3.2. Mixture

Contains the following hazardous ingredients or ingredients with a workplace exposure limit

Chemical Name	Conc.	CAS No.	EC No.	Classification according to Regulation (EC) No 1278/2008 (CLP).	SCL/ M-Factor/ ATE	REACH Registration Number	WEL/ OEL
White Smoke Dye	5%	84-54-8	201-539-6	Skin Sens. H317	-	-	UK
Potassium chlorate	10 -15% w/w	3811-04-9	223-289-7	Ox. Liq. H271; Acute Tox. H302; Acute Tox 4 H332; Aquatic Chronic 2, H411	-	01- 2119494917- 18-xxxx	No
Talc*	65-75%	14807-96-6	238-877-9	Non-Hazardous	-	Reach exempt	Yes

^{*} Substance with a workplace exposure limit

SECTION 4: FIRST AID MEASURES

Rescuers should take suitable precautions to avoid becoming casualties themselves

4.1 Description of First Aid Measures General Advice:

Show this safety data sheet to the doctor in attendance

Contact with eyes:

If substance has got into eyes, immediately wash out with plenty of water for several minutes. Irrigate eyes thoroughly whilst lifting eyelids.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention

Contact with skin:

Take off contaminated clothing and wash it before reuse.

Wash affected area with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Inhalation:

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

If unconscious, place person in recovery position

Apply artificial respiration only if patient is not breathing but **do not** use mouth to mouth resuscitation. Get immediate medical advice/attention.

Ingestion:

Rinse mouth with water (do not swallow).

Give 200-300mls (half pint) water to drink.

Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Contact with skin

- May cause redness and irritation.
- In cases of severe exposure, blistering of the skin may develop.

4.3. Immediate Medical Attention

In case of doubt or if the symptoms persist, call a doctor and show him the label and the safety data sheet. In case of accident, the first aid must be provided by qualified personnel to avoid further complications

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media:

Suitable extinguishing media:

Sand/earth; foam; water spray; carbon dioxide.

Unsuitable extinguishing media:

Do not use water jets; Dry agent extinguishers are unsuitable and should not be used.

5.2. Special Hazards arising from the mixture:

- Ignites readily.
- Contains an oxidising agent; may assist combustion.
- May form explosive dust/air mixtures.

5.3. Advice for fire-fighters:

- Collect contaminated fire extinguishing water separately. This MUST not be discharged into drains. Prevent fire extinguishing water from contaminating surface or ground water.
- Special protective equipment: Wear self-contained breathing apparatus (SCBA). Wear full protective clothing including chemical protection suit.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures:

- No action shall be taken involving any personal risk or without suitable training.
- Only trained and authorised personnel should carry out emergency response.
- Avoid formation of dust.
- Shut off all ignition sources
- Personal precautions for non-emergency personnel: Avoid breathing dust/fume/; Avoid contact with skin and eyes; Wear protective clothing as per section 8; Wash thoroughly after handling; Eyewash bottles should be available.
- Personal precautions for emergency responders: Evacuate the area and keep personnel upwind; Wear chemical protection suit; Wear self-contained breathing apparatus (SCBA).

6.2. Environmental precautions:

- Avoid release to the environment.
- Do not allow to enter public sewers and watercourses.
- If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities.

6.3. Methods and material for containment and cleaning up:

- Do not absorb spillage in sawdust or other combustible material.
- Avoid formation of dust.
- Shut off all ignition sources.
- Take action to prevent static discharges.
- Do not allow to enter public sewers and watercourses.
- Small spills Wipe up spillage with damp absorbent cloth or towel.
- Large spills Evacuate the area and keep personnel upwind.

Damp down to avoid dust generation.

Absorb spillage in earth or sand.

Sweep or shovel-up spillage and remove to a safe place.

Place in appropriate container.

Seal containers and label them.

Remove contaminated material to safe location for subsequent disposal.

Ventilate the area and wash spill site after material pick-up is complete.

6.4. Reference to other sections:

- See section(s): 7, 8 & 13

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

- Read the label before use.
- Prevent formation of dust.
- Take precautionary measures against static discharges.
- Ensure adequate ventilation.
- In case of inadequate ventilation wear respiratory protection.
- Avoid contact with skin and eyes.
- Do not eat, drink or smoke when using this product.
- Keep away from heat and sources of ignition. Avoid contact with acids and alkalis.
- Avoid release of powder to the environment.
- Take off contaminated clothing.
- Contaminated work clothing should not be allowed out of the workplace.
- Contaminated clothing should be laundered before reuse.
- Eyewash bottles should be available.

7.2. Conditions for storage, including any incompatibilities

- Shelf life: 2 years when stored in the original unopened sales container at ambient temperatures.
- Store in a cool, dry well-ventilated place. Keep container tightly closed.
- Keep away from combustible material.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep out of reach of children.

7.3. Specific end use

An airflow marking smoke generator

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

- For currently recommended monitoring procedures, see HSE series 'Methods for the Determination of Hazardous Substances' (MDHS).

-White Smoke Dye

UK HSE EH40 workplace exposure limits: Total inhalable dust 10mg/m3 (8-hour TWA) Respirable dust 4 mg/m3 (8-hour TWA)

- Potassium chlorate

DNEL (inhalational) 5.76 mg/m3 Industry, Long Term, Systemic Effects

DNEL (dermal) 3.5 mg/kg (bw/day) Industry, Long Term, Systemic Effects

DNEL (inhalational) 300 ug/m3 Consumer, Long Term, Systemic Effects

DNEL (dermal) 130 ug/kg (bw/day) Consumer, Long Term, Systemic Effects

DNEL (oral) 60 ug/kg (bw/day) Consumer, Long Term, Systemic Effects

PNEC aqua (freshwater) 1.15 mg/l

PNEC agua (marine water) 1.15 mg/l

PNEC (STP) 115 mg/l

PNEC terrestrial (soil) 3.83 mg/kg

Workplace Exposure Limits (WEL) for talc: Austria 5 mg/m³, Belgium 2 mg/m³, Bulgaria 3 mg/m³, Czech Republic 2 mg/m³, Denmark 5 mg/m³, Finland 2 mg/m³, France 5 mg/m³, Germany 2 mg/m³, Greece 2 mg/m³, Hungary 2 mg/m³, Ireland 0,8 mg/m³, Italy 2 mg/m³, Lithuania 1 mg/m³, Luxembourg 2 mg/m³, Netherlands 0,25 mg/m³, Norway 2 mg/m³, Poland 1 mg/m³, Portugal 2 mg/m³, Romania 2 mg/m³, Slovakia 2 mg/m³, Slovenia 2 mg/m³, Spain 2 mg/m³, Sweden 1 mg/m³, Switzerland 2 mg/m³, UK 1 mg/m³

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION (....)

8.2. Exposure controls

- Selection and use of personal protective equipment should be based on a risk assessment of exposure potential.
- Respiratory protection

If exposure to smoke is likely than wear suitable respiratory equipment.

Where a reusable half mask respirator is required, use EN 140, with gas/vapour filter EN 14387 type ABEK, or EN 405; EN 1827 and EN 143 particle filter.

Where a full face mask respirator is required, use EN 136, with gas/vapour filter EN 14387 type ABEK and particle filter EN 143.

- Skin protection

Wear suitable protective clothing.

Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and standard EN 374. The selection of a suitable glove depends on work conditions and whether the product is present on its own or in combination with other substances. Breakthrough time is dependent on the characteristics of the brand of glove used and the supplier should be consulted. PVC or rubber gloves are recommended.

- Hygiene measures

Contaminated clothing should be laundered before reuse.

Do not eat, drink or smoke when using this product.

Eyewash bottles should be available.

- Environmental exposure controls

Avoid release of powder to the environment.

Do not empty powder into drains









SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical State: Powder in a plastic or metal pot

Colour:Off-white.Odour:Odourless.Melting Point:Not applicable.Boiling point:Not applicable.

Flammability: Powder not flammable. Smoke may be flammable.

Flash-Point: Does not flash.

Autoignition temperature Not available

Decomposition temperature: Not available.

pH-value (quant.): Not available

Solubility: Partly soluble in/with water.

Partition coeff. (n-octanol/water):
Vapour pressure:

Density:
Not available
Not available
Not available
No data available

Oxidizing properties: Contains an oxidising agent; may assist combustion.

Energy Explosive properties Not applicable

9.2 Other Information:

Oxidizing properties: Contains an oxidising agent; may assist combustion.

Energy Explosive properties Not applicable

- No information available

SECTION 10. STABILITY AND REACTIVITY

- 10.1 Reactivity
- No hazardous reactions known if used for its intended purpose
- 10.2 Chemical stability
- Considered stable under normal conditions.
- 10.3 Possibility of hazardous reactions
- Reacts with combustible material.
- Reacts with acids liberating toxic gas (chlorine).
- 10.4 Conditions to avoid
- Avoid formation of dust.
- Keep away from heat and sources of ignition.
- Keep away from static electricity.
- 10.5 Incompatible materials
- Incompatible with strong acids.
- Incompatible with alkalis (strong bases).
- Incompatible with halogenated substances.
- 10.6 Hazardous decomposition products
- Decomposition products may be toxic

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute Toxicity

Based on available data, the classification criteria are not met.

Chemical name	LD50 (oral, rat)	LC50 (inhalation, rat)	LD50 (dermal, rabbit)
Potassium chlorate	500 mg/kg	5 mg/l (4 hr)	NS
White Smoke Dye	No data	No data	No data

- Skin corrosion/irritation

Based on available data, the classification criteria are not met.

- Serious eye damage/irritation

Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

Classification based on calculation and concentration thresholds.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity No evidence of reproductive effects
- Specific target organ toxicity (STOT) single exposure Based on available data, the classification criteria are not met.

SECTION 11. TOXICOLOGICAL INFORMATION (....)

- Specific target organ toxicity (STOT) repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard
 Based on available data, the classification criteria are not met.
- Contact with eyes
 May cause redness and swelling.
- Contact with skin
 May cause redness and irritation.
 In cases of severe exposure, blistering of the skin may develop.
- Ingestion
 May cause discomfort, nausea/vomiting.
- Inhalation Causes shortness of breath. May cause coughing and tightness of chest.

11.2 Information on other hazards

-No further information

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

- Harmful to aquatic life with long lasting effects.
- Classification based on calculation and concentration thresholds.
- Potassium chlorate
 LC50 (fish) 1 g/l (4 days)
 EL50 (aquatic invertebrate)

EL50 (aquatic invertebrates) 1 g/l (48 hr)

EL50 (aquatic algae) 1.9 - 500 mg/l (72 hr)

12.2 Persistence and degradability

- Potassium chlorate Biodegradable

12.3 Bio accumulative potential

- Chlorate is converted to chlorite in plants, which accumulates in cells until toxic concentrations are reached, when the plant dies

12.4 Mobility in soil

- No information available

12.5 Results of PBT and vPvB assessment

Not determined

12.6 Endocrine disrupting properties

- No information available

12.7 Other adverse effects

- No information available

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

- Do not discharge into drains or the environment, dispose to an authorised waste collection point
- Dispose of product and packaging in accordance with national waste regulations.
- This material and/or its container must be disposed of as hazardous waste.

13.2 Classification

- The waste must be identified according to the List of Wastes (2000/532/EC).
- Hazardous Property Code(s): HP 4 Irritant; HP 14 Ecotoxic

SECTION 14. TRANSPORT INFORMATION

Not classified as hazardous for transport

14.1 UN number

- UN No.: Not applicable

14.2 UN proper shipping name

- Proper Shipping Name: Not applicable

14.3 Transport hazard class(es)

- Hazard Class: Not applicable

14.4 Packing group

- Packing Group: Not applicable

14.5 Environmental hazards

- Not Classified

14.6 Special precautions for user

- Not Classified

14.7 Maritime transport in bulk according to IMO instruments

- Not applicable

14.8 Road/Rail (ADR/RID)

- Proper Shipping Name: Not applicable
- ADR UN No.: Not applicable
- ADR Hazard Class: Not applicable
- ADR Packing Group: Not applicable
- Tunnel Code: Not applicable

14.9 Sea (IMDG)

- Proper Shipping Name: Not applicable
- IMDG UN No.: Not applicable IMDG Hazard Class: Not applicable
- IMDG Pack Group.: Not applicable

14.10 Air (ICAO/IATA)

- Proper Shipping Name: Not applicable
- ICAO UN No.: Not applicable ICAO Hazard Class: Not applicable -

ICAO Packing Group: Not applicable

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- This safety data sheet is provided in compliance with REACH Regulation (EC) No 1907/2006 as amended by Regulation (EU) 2020/878.
- Regulation (EC) No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) applies in Europe.
- The COSHH Regulations apply in the UK.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Information contained in this data sheet is accurate to the best of our knowledge and belief and is given in good faith. It is intended to describe our product from the point of view of safety requirements and is not intended to guarantee any particular properties.

Sources of data: Information from published literature and supplier safety data sheets

Revision No. 1.1. Review and amendment of headers to meet UK REACH requirements..

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP];

Sens Skin. 1. H317: Classification based on calculation and concentration thresholds Aquatic Chronic 3, H412: Classification based on calculation and concentration thresholds

Text not given with phrase codes where they are used elsewhere in this safety data sheet:

- H271: May cause fire or explosion; strong oxidiser
- H302: Harmful if swallowed
- H332: Harmful if inhaled
- H411: Toxic to aquatic life with long lasting effects

Acronyms

- ATE: Acute Toxicity Estimates
- CAS: Chemical Abstracts Service
- DNEL: Derived No-Effect Level
- EC: European Community
- EC50: Effective Concentration, 50%
- GHS: Globally Harmonised System
- IARC: International Agency for Research on Cancer
- IC50: Half-maximal inhibitory concentration
- LC50: Lethal Concentration, 50%
- LD50: Lethal Dose, 50%
- NOAEC: No observed adverse effect concentration
- NOAEL: No observed adverse effect level
- NOEC: No observed effect concentration
- OEL: Occupational Exposure Limit
- PBT: Persistent, Bioaccumulative and Toxic
- PNEC: Predicted No-Effect Concentration
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- vPvB: very Persistent and very Bioaccumulative
- WEL: Workplace Exposure Limit

Previous revisions should be destroyed.